




MP201612A Series



1. Features:


- 0806 Foot print (2.0x1.6 mm), 1.2mm Max. height SMD Power Inductor for high frequency application.
- Inductance range from 0.47uH to 2.2uH.
- High saturation current characteristics by distributed gapped metal dust core.
- Ideal for portable device, PAD, Notebook, smart phone & High Density DC to DC converter Board.
- Lower DC resistance for higher current application.
- Max. Withstand Voltage: 25V DC
- Working Frequency up to 5Mhz.
- Tape & Reel Quantity: 3,000 piece per 6 inches reel.
- Operating Temperature Range -40°C to + 85°C.



2. Electrical Characteristics:

ITG Part Number	OCL (uH) ±30%	DCR (mΩ) Typ.	DCR (mΩ) Max.	I _{rms} (AMP)	I _{sat1} (Amp)
MP201612A-R47NHF	0.47	37	45	3.50	3.60
MP201612A-1R0NHF	1.00	68	78	2.50	2.70
MP201612A-1R5NHF	1.50	95	114	1.80	2.00
MP201612A-2R2NHF	2.20	155	170	1.50	1.80

3. Mechanical Dimensions (unit: mm):




A ±	B ±	C	D ±
0.20	0.20	Max.	0.30
2.00	1.60	1.20	0.50

Notes:

1. Open Circuit Inductance(OCL), L@ I_{rms} and L @ I_{sat} are measured at 100KHz, 1.0V, (T_a=25°C).
2. I_{sat1}: DC current that causes inductance to drop approximately by 30% from OCL.
3. I_{rms}: DC current for an approximate temperature rise of 40°C without core loss. Derating is necessary for AC currents, PCB pad layout, trace thickness and width, air-flow and proximity of other heat generating components will affect the temperature rise. It is recommended the part temperature not exceed 85°C under worst case operating conditions verified in the end application.
4. Inductance vs. DC Current vs. Temperature Curve, please see the next pages for more detail information.

Recommended PCB Layout (Unit mm)





MP201612A Series



4. Inductance vs. Current vs. Temperature

