




SL1618 Series



1. Features:

- Ferrite based SMD Inductor with lower core loss.
- Custom values are welcomed.
- High current output chokes, upto 30.0 Amp with approx. 20% roll off.
- Low Profile 4.5mm Max. height .
- Foot Print 4.1 x 4.0 mm Max.
- Ideal for Buck Converter, VRM & High Density Board Design.
- Operating frequency up to 1 MHz application.
- Operating Temperature Range -55°C to + 130°C , RoHs & HF compliance .




2. Electrical Characteristic of SL1618 Series:

Part Number	Inductance (uH) ±15%	DCR (mΩ) ± 9.0%	Isat ¹ (A) @25°C	Isat ² (A) @75°C	Isat ³ (A) @100°C	Irms (A) @25°C
SL1618A-R065LHF	0.065	0.25	30.0	25.0	22.0	24.0
SL1618B-R065LHF	0.065	0.29	30.0	25.0	22.0	22.0

3. Mechanical Dimension(Unit:mm):

A	B	C	D	E	F	G	H
Max.	Max.	Max.	Max.	Nom.	Nom.	Nom.	Ref.
4.00	3.95	4.50	4.10	1.20	1.00	1.30	0.45



Note:

- 1>.Open Circuit Inductance (OCL) test condition:100KHz,0.1Vrms,0Adc ,at 25°C .
- 2>.Full Load Inductance (FLL) Test condition:100KHz,0.1Vrms ,Isat ;(Ta=25°C).
- 3>.Isat¹Isat² & Isat³ : DC current that will cause inductance to drops approximately by 20% ;
- 4>. Irms: DC current for an approximate temperature rise of 40°C without core loss,.Derating is necessary for AC currents. PCB pad layout,trace thickness and width,air-flow and proximity of other heat generating components will affect the temperature rise. It is recommended the part temperature not exceed 130°C under worst case operating conditions verified in the end application.
- 5>.The nominal DCR is measured from point "a" to point"b",as shown above on the mechanical drawing.

4. Inductance Characteristics (Inductance vs. Current):

